Northfork Beer Master Machine Glass Wash

ACCO Brands Australia Pty Ltd

Version No: 1.3 Safety Data Sheet according to WHS and ADG requirements

Issue Date: 15/04/2021

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

| Product name | Northfork Beer Master Machine Glass Wash | |
|-------------------------------|--|--|
| Synonyms | t Available | |
| Other means of identification | 5L - 637120700 | |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Detergent for machine washing of glasses |
|--------------------------|--|
| | |

Details of the supplier of the safety data sheet

| Registered company name | ACCO Brands Australia Pty Ltd | |
|-------------------------|--|--|
| Address | 17-19 Waterloo Street, Queanbeyan 2620 NSW Australia | |
| Telephone | +61-2-96740900 | |
| Fax | +61-2-96740910 | |
| Website | www.accobrands.com.au | |
| Email | sds.anz@acco.com | |

Emergency telephone number

| Association / Organisation | Poisons Information Line |
|-----------------------------------|--------------------------|
| Emergency telephone numbers | 13 11 26 |
| Other emergency telephone numbers | 13 11 26 |

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

| Poisons Schedule | Not Applicable | |
|-------------------------------|--|--|
| Classification ^[1] | Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation) | |
| Legend: | Legend: 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI | |

Label elements

GHS label elements





SIGNAL WORD

DANGER

Hazard statement(s)

| H314 | Causes severe skin burns and eye damage | |
|------|---|--|
| H318 | Causes serious eye damage | |
| H335 | 35 May cause respiratory irritation | |

Precautionary statement(s) Prevention

| P101 | If medical advice is needed, have product container or label at hand. | | |
|------|---|--|--|
| P102 | Keep out of reach of children. | | |
| P103 | Read label before use. | | |

Version No: **1.3** Page **2** of **10** Issue Date: **15/04/2021**

Beer Master Machine Glass Wash

| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. | |
|------|---|--|
| P271 | Use only outdoors or in a well-ventilated area. | |
| P280 | P280 Wear protective gloves/protective clothing/eye protection/face protection. | |

Precautionary statement(s) Response

| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. | |
|----------------|--|--|
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P310 | Immediately call a POISON CENTER or doctor/physician. | |
| P363 | Wash contaminated clothing before reuse. | |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. | |

Precautionary statement(s) Storage

| P405 | Store locked up. | |
|-----------|--|--|
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. | |

Precautionary statement(s) Disposal

| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|
|------|---|

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|------------|-----------|---|
| 141-43-5 | <10 | <u>monoethanolamine</u> |
| 96910-36-0 | <10 | isooctylphenol, ethoxylated, propoxylated |
| 5064-31-3 | <10 | nitrilotriacetic acid, trisodium salt |
| 13590-71-1 | <10 | phosphonic acid, monomethyl ester |

SECTION 4 FIRST AID MEASURES

Description of first aid measures

| Eye Contact | If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|---|
| Skin Contact | If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. |
| Ingestion | For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Beer Master Machine Glass Wash

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances. In such an event consider:

- ▶ foam.
- dry chemical powder.carbon dioxide.

Special hazards arising from the substrate or mixture

| Fire Incompatibility | None known. | | |
|-------------------------|--|--|--|
| Advice for firefighters | | | |
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. | | |
| Fire/Explosion Hazard | The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic furnes of carbon monoxide (CO). May emit acrid smoke. Decomposes on heating and produces toxic furnes of; carbon dioxide (CO2) other pyrolysis products typical of burning organic materialMay emit poisonous furnes. May emit corrosive furnes. | | |

SECTION 6 ACCIDENTAL RELEASE MEASURES

| Personal | precautions, | protecti | ve equ | ipment | and | emergency | procedi | ures |
|----------|--------------|----------|--------|--------|-----|-----------|---------|------|
| | | | | | | | | |

| Minor Spills | Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. |
|--------------|--|
| Major Spills | Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

| Precautions for safe hand | recautions for safe nandling | | | | |
|---------------------------|--|--|--|--|--|
| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. DO NOT allow clothing wet with material to stay in contact with skin | | | | |
| Other information | | | | | |

Conditions for safe storage, including any incompatibilities

| Suitable container | Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. |
|-------------------------|---|
| Storage incompatibility | Formaldehyde: • is a strong reducing agent • may polymerise in air unless properly inhibited (usually with methanol up to 15%) and stored at controlled temperatures • will polymerize with active organic material such as phenol • reacts violently with strong oxidisers, hydrogen peroxide, potassium permanganate, acrylonitrile, caustics (sodium hydroxide, yielding formic acid and flammable hydrogen), magnesium carbonate, nitromethane, nitrogen oxides (especially a elevated temperatures), peroxyformic acid • is incompatible with strong acids (hydrochloric acid forms carcinogenic bis(chloromethyl)ether*), amines, ammonia, aniline, bisulfides, gelatin, iodine, magnesite, phenol, some monomers, tannins, salts of copper, iron, silver. • acid catalysis can produce impurities: methylal, methyl formate Aqueous solutions of formaldehyde: • slowly oxidise in air to produce formic acid • attack carbon steel |

Version No: 1.3 Page 4 of 10 Issue Date: 15/04/2021

Beer Master Machine Glass Wash

Concentrated solutions containing formaldehyde are:

- unstable, both oxidising slowly to form formic acid and polymerising; in dilute aqueous solutions formaldehyde appears as monomeric hydrate (methylene glycol) - the more concentrated the solution the more polyoxymethylene glycol occurs as oligomers and polymers (methanol and amine-containing compounds inhibit polymer formation)
- readily subject to polymerisation, at room temperature, in the presence of air and moisture, to form paraformaldehyde (8-100 units of formaldehyde), a solid mixture of linear polyoxymethylene glycols containing 90-99% formaldehyde; a cyclic trimer, trioxane (CH2O3), may also form

Flammable and/or toxic gases are generated by the combination of aldehydes with azo, diazo compounds, dithiocarbamates, nitrides, and strong reducing agents

*The empirical equation may be used to determine the concentration of bis(chloromethyl)ether (BCME) formed by reaction with HCl:

 $log(BCME)ppb = -2.25 + 0.67 \cdot log(HCHO) ppm + 0.77 \cdot log(HCI)ppm$

Assume values for formaldehyde, in air, of 1 ppm and for HCl of 5 ppm, resulting BCME concentration, in air, would be 0.02 ppb.

Monoethanolamine

- is a strong organic base
- reacts violently with strong oxidisers, strong acids (with spattering)
- is incompatible with acetic acid, acetic anhydride, acrolein, acrylates, acrylic acid, acrylonitrile, alcohols, aldehydes, alkali metals, alkylene oxides, substituted allyls, caprolactam solution, cellulose nitrate, chlorosulfonic acid, cresols, epichlorohydrin, glycols, halogenated hydrocarbons, isocyanates, ketones, mesityl oxide, oleum, organic anhydrides, phenols, beta-propiolactone, vinyl acetate
- ▶ forms explosive mixture with sodium perchlorate
- ► reacts with iron forming tris-ethanolamineiron
- ▶ may undergo a self-sustaining thermal decomposition when heated in excess of 250 degrees C
- ▶ attacks aluminium, copper, lead, tin, zinc, and their alloys
- attacks plastics, coatings an rubber

None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|------------------|---------------|-------------------|------------------|---------------|---------------|
| Australia Exposure Standards | monoethanolamine | Ethanolamine | 7.5 mg/m3 / 3 ppm | 15 mg/m3 / 6 ppm | Not Available | Not Available |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|---------------------------------------|--|-----------|-----------|-----------|
| monoethanolamine | Ethanolamine | 6 ppm | 6 ppm | 1000 ppm |
| nitrilotriacetic acid, trisodium salt | Nitrilotriacetic acid, trisodium salt, monohydrate | 9.2 mg/m3 | 100 mg/m3 | 110 mg/m3 |

| Ingredient | Original IDLH | Revised IDLH |
|---|---------------|---------------|
| monoethanolamine | 1,000 ppm | 30 ppm |
| isooctylphenol, ethoxylated, propoxylated | Not Available | Not Available |
| nitrilotriacetic acid, trisodium salt | Not Available | Not Available |
| phosphonic acid, monomethyl ester | Not Available | Not Available |

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Appropriate engineering controls

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Local exhaust ventilation usually required

Personal protection











Personal protection

► Chemical goggles

Full face shield may be required for supplementary but never for primary protection of eyes.

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.

Skin protection

See Hand protection below

► Wear chemical protective gloves, e.g. PVC.

Hands/feet protection

Wear safety footwear or safety gumboots, e.g. Rubber
 When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

NOTE:

The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid

Version No: **1.3** Page **5** of **10** Issue Date: **15/04/2021**

Beer Master Machine Glass Wash

▶ all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact. ► chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). ▶ When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. ▶ When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. ▶ Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. **Body protection** See Other protection below Overalls. ► P.V.C. apron. Other protection Barrier cream. Skin cleansing cream. Eye wash unit. Thermal hazards Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Beer Master Machine Glass Wash

| Material | CPI |
|------------------|-----|
| BUTYL | A |
| NEOPRENE | A |
| VITON | Α |
| BUTYL/NEOPRENE | С |
| HYPALON | С |
| NATURAL RUBBER | С |
| NATURAL+NEOPRENE | С |
| NEOPRENE/NATURAL | С |
| NITRILE | С |
| NITRILE+PVC | С |
| PVA | С |
| PVC | С |

^{*} CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type ABEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|---------------------------------------|-------------------------|--------------------------|-------------------------------|
| up to 10 x ES | ABEK-AUS P2 | - | ABEK-PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | ABEK-AUS / Class 1 P2 | - |
| up to 100 x ES | - | ABEK-2 P2 | ABEK-PAPR-2 P2 ^ |

^ - Full-face

 $A(All\ classes) = Organic\ vapours,\ B\ AUS\ or\ B1 = Acid\ gasses,\ B2 = Acid\ gas\ or\ hydrogen\ cyanide(HCN),\ E = Sulfur\ dioxide(SO2),\ G = Agricultural\ chemicals,\ K = Ammonia(NH3),\ Hg = Mercury,\ NO = Oxides\ of\ nitrogen,\ MB = Methyl\ bromide,\ AX = Low\ boiling\ point\ organic\ compounds(below\ 65\ degC)$

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| Appearance | A clear liquid | | | |
|--|----------------|---|---------------|--|
| Physical state | Liquid | Relative density (Water = 1) | 1.00-1.05 | |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available | |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available | |
| pH (as supplied) | 10-12 | Decomposition temperature | Not Available | |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available | |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Available | |

Beer Master Machine Glass Wash

| Flash point (°C) | Not Available | Taste | Not Available |
|---------------------------|---------------|----------------------------------|---------------|
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Available | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water (g/L) | Miscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| Reactivity | See section 7 |
|------------------------------------|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

propoxylated

Inhalation (rat) LC50: >1 mg/l/8h]^[2]

Oral (rat) LD50: 3200 $mg/kgt^{[2]}$

| Inhaled | The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Not normally a hazard due to non-volatile nature of product The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence. | | |
|---------------------------|--|---------------|--|
| Ingestion | The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Ethanolamine is an intermediate metabolites of certain animal producing phospholipids and choline. In poisoned rats, monoethanolamine may cause excessive tear secretion, hair erection, defective vertebral curvature, unsteady gait, weight loss, discharge around the eye, anus and genitalia. | | |
| Skin Contact | The material can produce chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Oral and skin exposure to ethanolamine may produce weakness, abdominal distension, emaciation and damage to the respiratory tract, intestines, thymus, kidneys and the skin (ulceration and burn like effect). These are worse with skin exposure due to a high absorption rate. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. | | |
| Еуе | The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. A drop of ethanolamine into eye causes injury slightly less than that produced by ammonia say grade 9, on a 1 to10 scale, but that into the rabbit eyes (0.005 ml) caused severe eye injury with vascularisation, deformation, severe iris inflammation and conjunctival irritation. | | |
| Chronic | Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population. There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population. | | |
| _ | | | |
| Beer Master Machine Glass | TOXICITY | IRRITATION | |
| Wash | Not Available | Not Available | |

| Beer Master Machine Glass Wash | TOXICITY | IRRITATION | |
|-----------------------------------|---|------------------------------------|------------|
| | Not Available | Not Available | |
| | TOXICITY | IRRITATION | |
| monoethanolamine | Dermal (rabbit) LD50: 1020 mg/kg ^[2] | Eye (rabbit): 0.76 mg - SEVERE | |
| | Oral (rat) LD50: 1091.4 mg/kg ^[1] | Skin (rabbit):505 mg open-moderate | |
| | | | |
| | TOXICITY | | IRRITATION |
| isooctylphenol, ethoxylated, | dermal (rat) LD50: >5000 mg/kgt ^[2] | | [BASF] |

Eye (rabbit): irritant

Skin (rabbit): irritant

Version No: 1.3 Page 7 of 10 Issue Date: 15/04/2021

Beer Master Machine Glass Wash

| nitrilotriacetic acid, trisodium salt | TOXICITY Oral (rat) LD50: 300 mg/kg ^[1] | IRRITATION * [BASF] Eye (rabbit): Irritant * Skin (rabbit): non-irritating * | |
|--|---|---|--|
| phosphonic acid, monomethyl ester | Oral (rat) LD50: 1740 mg/kgE ^[2] | IRRITATION Eye (rabbit): 0.05 mg/24h-SEVERE Skin (rabbit): 0.75 mg/24h-SEVERE | |
| Legend: | Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | | |

Beer Master Machine Glass Wash

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. No significant acute toxicological data identified in literature search.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

While it is difficult to generalise about the full range of potential health effects posed by exposure to the many different amine compounds, characterised by those used in the manufacture of polyurethane and polyisocyanurate foams, it is agreed that overexposure to the majority of these materials may cause adverse health effects.

- Many amine-based compounds can induce histamine liberation, which, in turn, can trigger allergic and other physiological effects, including bronchoconstriction or bronchial asthma and rhinitis.
- Systemic symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, tachycardia (rapid heartbeat), itching, erythema (reddening of the skin), urticaria (hives), and facial edema (swelling). Systemic effects (those affecting the body) that are related to the pharmacological action of amines are usually transient.

Typically, there are four routes of possible or potential exposure: inhalation, skin contact, eye contact, and ingestion. **Inhalation:**

Inhalation

MONOETHANOLAMINE

Inhalation of vapors may, depending upon the physical and chemical properties of the specific product and the degree and length of exposure, result in moderate to severe irritation of the tissues of the nose and throat and can irritate the lungs.

Products with higher vapour pressures have a greater potential for higher airborne concentrations. This increases the probability of worker exposure. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

* Bayer

ISOOCTYLPHENOL, ETHOXYLATED, PROPOXYLATED

Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products. Exposure to these chemicals can occur through ingestion, inhalation, or contact with the skin or eyes. Studies of acute toxicity show that volumes well above a reasonable intake level would have to occur to produce any toxic response. Moreover, no fatal case of poisoning with alcohol ethoxylates has ever been reported. Multiple studies investigating the acute toxicity of alcohol ethoxylates have shown that the use of these compounds is of low concern in terms of oral and dermal toxicity.

Clinical animal studies indicate these chemicals may produce gastrointestinal irritation such as ulcerations of the stomach, pilo-erection, diarrhea, and lethargy. Similarly, slight to severe irritation of the skin or eye was generated when undiluted alcohol ethoxylates were applied to the skin and eyes of rabbits and rats. The chemical shows no indication of being a genotoxin, carcinogen, or mutagen (HERA 2007).

Both laboratory and animal testing has shown that there is no evidence for alcohol ethoxylates (AEs) causing genetic damage, mutations or cancer. No adverse reproductive or developmental effects were observed.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

for similar material isooctylphenol, ethoxylated (BASF Citowett)

Nitrilotriacetic acid and its water-soluble metal complexes occur in household detergents and drinking water. Their ability to chelate metal ions accounts for the toxicity. They may cause cancer of the kidney, bladder and urinary tract in some experimental animals but no foetal or genetic damage has been recorded. They do not cause skin sensitisation or irritation but may accumulate in the foetal skeleton.

In humans, they are poorly absorbed from the intestines and rapidly excreted in the urine.

NITRILOTRIACETIC ACID, TRISODIUM SALT

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

Version No: **1.3** Page **8** of **10** Issue Date: **15/04/2021**

Beer Master Machine Glass Wash

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

PHOSPHONIC ACID, MONOMETHYL ESTER

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, couch and mucus production.

| Acute Toxicity | 0 | Carcinogenicity | 0 |
|--------------------------------------|----------|--------------------------|---|
| Skin Irritation/Corrosion | * | Reproductivity | 0 |
| Serious Eye Damage/Irritation | * | STOT - Single Exposure | 0 |
| Respiratory or Skin sensitisation | 0 | STOT - Repeated Exposure | 0 |
| Mutagenicity | 0 | Aspiration Hazard | 0 |

Legend:

X – Data available but does not fill the criteria for classification

✓ – Data required to make classification available

O - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

| Ingredient | Endpoint | Test Duration (hr) | Species | Value | Source |
|--|--|--------------------|-------------------------------|----------------|--------|
| monoethanolamine | LC50 | 96 | Fish | =75mg/L | 1 |
| monoethanolamine | EC50 | 48 | Crustacea | 32.6mg/L | 2 |
| monoethanolamine | NOEC | 504 | Crustacea | 0.85mg/L | 2 |
| monoethanolamine | EC50 | 72 | Algae or other aquatic plants | 2.1mg/L | 2 |
| monoethanolamine | EC50 | 72 | Algae or other aquatic plants | ca.2.5mg/L | 2 |
| nitrilotriacetic acid, trisodium salt | LC50 | 96 | Fish | <16.9-20.2mg/L | 1 |
| nitrilotriacetic acid, trisodium salt | EC50 | 48 | Crustacea | 560- 1000mg/L | 2 |
| nitrilotriacetic acid, trisodium salt | EC50 | 72 | Algae or other aquatic plants | >91.5mg/L | 2 |
| nitrilotriacetic acid, trisodium salt | NOEC | 72 | Algae or other aquatic plants | 1.43mg/L | 2 |
| Legend: | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data | | | | |

For monoethanolamine: log Kow: -1.31; Koc: 5 Half-life (hr); air: 11 Henry's atm m3 /mol: 4.00E-08; BOD 5: 0.8-1.1,0%; Biodegradability: BOD5: 800 mg/g>70%: BOD of the ThOD (OECD 301F)>90%: DOC reduction (OECD 301A) COD: 1.27-1.28ThOD: 2.49BCF: <1.

Environmental Fate: Monoethanolamine will leach into soil. It is expected to exist solely as a vapor in the ambient atmosphere. Models estimate that this material will preferentially partition to water versus air or soil.. Vapour-phase is degraded in the atmosphere by reaction with photochemically produced hydroxyl radicals. The potential for mobility in the soil is high.

Degradation and Persistence: The material is readily biodegradable, and will biodegrade relatively rapidly in both soil and water, and will not persist in the environment. Monoethanolamine is

biodegraded or transformed into other compounds under both aerobic and anaerobic conditions even at concentrations greater than 1500 mg/kg.

DO NOT discharge into sewer or waterways

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------------|-------------------------|------------------|
| monoethanolamine | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------------|----------------------|
| monoethanolamine | LOW (LogKOW = -1.31) |

Mobility in soil

| Ingredient | Mobility |
|------------------|----------------|
| monoethanolamine | HIGH (KOC = 1) |

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Version No: **1.3** Page **9** of **10** Issue Date: **15/04/2021**

Beer Master Machine Glass Wash

- ► Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- ► Reuse
- ▶ Recycling
- ► Disposal (if all else fails)

Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ► DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible.
- ► Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- ► Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material).
- ▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required

| Marine Pollutant | NO |
|------------------|----------------|
| HAZCHEM | Not Applicable |

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

MONOETHANOLAMINE(141-43-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

SOOCTYLPHENOL, ETHOXYLATED, PROPOXYLATED(96910-36-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

NITRILOTRIACETIC ACID, TRISODIUM SALT(5064-31-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System - Consolidated Lists Australia Inventory of Chemical Substances (AICS) International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

PHOSPHONIC ACID, MONOMETHYL ESTER(13590-71-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

| National Inventory | Status |
|----------------------------------|---|
| Australia - AICS | N (isooctylphenol, ethoxylated, propoxylated) |
| Canada - DSL | N (isooctylphenol, ethoxylated, propoxylated; phosphonic acid, monomethyl ester) |
| Canada - NDSL | N (isooctylphenol, ethoxylated, propoxylated; phosphonic acid, monomethyl ester; monoethanolamine; nitrilotriacetic acid, trisodium salt) |
| China - IECSC | N (isooctylphenol, ethoxylated, propoxylated; phosphonic acid, monomethyl ester) |
| Europe - EINEC / ELINCS / NLP | N (isooctylphenol, ethoxylated, propoxylated) |
| Japan - ENCS | N (isooctylphenol, ethoxylated, propoxylated; phosphonic acid, monomethyl ester) |
| Korea - KECI | N (isooctylphenol, ethoxylated, propoxylated; phosphonic acid, monomethyl ester) |
| New Zealand - NZIoC | N (phosphonic acid, monomethyl ester) |
| Philippines - PICCS | N (phosphonic acid, monomethyl ester) |
| USA - TSCA | N (isooctylphenol, ethoxylated, propoxylated; phosphonic acid, monomethyl ester) |
| Legend: | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

Beer Master Machine Glass Wash

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

| Name | CAS No |
|---------------------------------------|-----------------------|
| nitrilotriacetic acid, trisodium salt | 18662-53-8, 5064-31-3 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible Concentration-Short Term Exposure Limit}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.